

Aftercare and Maintenance Advice - External

All Rockpave resin bound surfacing systems are designed to provide attractive, durable and hard wearing pavements in a wide variety of applications and finishes.

To ensure your Rockpave installation is maintained in best condition, the following aftercare and maintenance provisions should be followed.

Cleaning

Rockpave surfaces should be regularly cleaned as necessary to maintain its appearance. Vacuum, sweep or blow excess dirt, dust and detritus from the surface. Wash contaminants and stains with water and detergent as necessary.

Pressure Washing

If pressure washing the surface, the maximum pressure should not exceed 1000psi on a fan type jet with cold water. Treat stains with a suitable detergent first prior to washing. If any stone dislodgement occurs, cleaning should be stopped immediately to prevent further damage and advice sought from the installer or MPS Paving Systems.

Chewing Gum Removal

Chewing Gum should be removed by scraping and or using a suitable proprietary removal solution. Users wishing to employ large scale commercial pressure washing or freeze method gum removal operations should first seek advice from MPS Paving Systems Pty Ltd.

Spillages

Oil and chemical spills should be cleaned immediately with water and suitable detergents.

Abrasion

Loss of gloss due to pedestrian and vehicular wear and abrasion may be restored by re-sealing with Rockpave UVS sealer

Power Steering

Users should not use vehicular power steering whilst stationary to avoid possible stone dislodgement.

Point Loading and Impact Damage

Users should avoid high impact point loading such as scaffolding, hydraulic vehicle or machinery supports and heavy impact damage such as skip removal.

Repairs

Damaged surfaces should be repaired as soon as possible using only Rockpave materials to the original installation specification and in accordance with the procedures detailed within the Rockpave Installation Manual.

The information detailed in this document is liable to modification or change at any time at the discretion of MPS Paving Systems Pty Ltd. MPS Paving Systems Pty Ltd advises customers and specifiers to consult with MPS Paving Systems Pty Ltd that the warranty advice document is the current issue. Any person or company using or specifying the product without first consulting MPS Paving Systems Pty Ltd or a Rockpave Approved Installer as to the suitability of the product for the intended use does so at their own risk. MPS Paving Systems Pty Ltd accepts no responsibility for the performance of the product, or for any loss or damage arising out of such use.